Installation Instructions for Round Picnic Table

Note: Handle ALL concrete parts carefully.

Step 1	First, determine the area where your table(s) are going to be installed. Each table is 67 inches in diameter.
Step 2	Using a two wheeled moving dolly, move the bottom leg (leg with a rectangle notch on the top) into position. Do not leave legs sitting upright unattended in case they should tip over causing damage or injury! Position a top leg (leg with a rectangle notch on the bottom) at the end of the bottom leg. Now install 2 seat brackets on each end of the leg using the 7" x ⅜" bolts, nuts and 4 fender washers per bolt. Just finger tight for now. Carefully lift the top leg over the bottom leg and into the notch on the bottom leg. (When lowering do not allow it to jam and don't force it down.)
Step 3	Install the large table top plate. (Keep rotating until the 2 holes line up with the holes in the legs. Insert 2 of the 7" bolts thru the holes in the legs. Use one of the fender washers on the steel bracket side and 2 or 3 on the concrete side. Now using a broom handle, line up the umbrella holes in the legs, then tighten the 7" bolts until the washers bend slightly.
Step 4	Now place the table top on the steel plate, slowly and carefully rotate the top until you line up one of the 4 inserts in the bottom of the table top with one of the holes in the steel plate. Then install one 1" x ¼" x ⅜" bolts with one fender washer. Adjust the table top until the other 3 holes line up and insert and install remaining 1" x ¼" x ⅜" bolts and fender washers. (Do NOT over tighten the bolts. ¼ turn past snug.)
Step 5	Install the seats one at a time using 4 of the 1 ¼" x ⅜" bolts per seat. Each of the 4 bolts should have a rubber washer sandwiched between 2 fender washers. Tighten these bolts carefully, until the rubber washer is slightly compressed.
Step 6	Be sure all the legs are touching the ground and not hung up or on uneven ground. If the site is uneven use shims to make the legs level.
Step 7	Level the seats and tighten the 7" bolts very tight, until the washers bend slightly.

Tri-Kon Precast Products Ltd.
601 Patterson Street West
Cranbrook BC V1C 6T3
250-426-8162
info@trikonprecast.com
trikonprecast.com

PRODUCT
Miscellaneous

DRAWING
Round Concrete Picnic Table Installation

WEIGHT

DRAWING NO.

DATE
As per drawing

SHEET
09 of 10

UNITS / SCALE
As per drawing

Request A Quote